




A Division of Pacific Brands Household
Products Pty Ltd
ABN 23 098 742 584

36 Commercial Drive, Private Bag 1499,
South Dandenong, Victoria, Australia 3164
Tel: 03 - 9215 2020 Fax: 03 - 9215 2015



MATERIAL SAFETY DATA SHEET

PRODUCT IDENTIFICATION

<u>Product Name:</u>	Flexible Polyurethane Foam AF and EM grades	U.N. Number:	None
<u>Other Names:</u>	Polyether urethane foam, flame retarded (combustion modified)	Dangerous Goods Class/and Subsidiary Risk:	None
		Hazchem Code:	None
		Poisons Schedule:	None

Manufacturer's Codes: AF50-140, AF55-300, AF60-200, LRGR45-100, LRGR45-50 and moulded foams, EM47-200.

Main Uses: AF & LRGR foams are used as cushion components in aircraft seating, EM grades are moulded cushions in office and other seating applications.

Physical Description/Properties

Appearance:	Flexible, cellular structure, white to off-white natural colour or specified colour. (Shade will change on exposure to air.)
Boiling Point:	Not applicable.
Melting/thermal decomposition range:	above 200°C
Vapour pressure:	None
Per cent volatiles:	None
Specific gravity:	Apparent density of 40 to 100 kg/m ³
Flash point:	Above 250°C
Flammability limits:	Material can be ignited by an open flame or by a source for smouldering ignition.
Autoignition temperature:	Above 260°C short term. Avoid long term exposure over 135°C.

Ingredients:

Chemical entity:	CAS No.:	Proportion:
Polyurethane foam	9009-54-5	High content (>60%)
Melamine	108-78-1	Medium Content (moulded foams)
Halo-phosphate	-	Low content
Graphite		Medium content (AF/LRGR foams)

Reaction product of toluene diisocyanate (AF/LRGR foams), water and polyether polyol. Some polyols may contain styrene acrylonitrile polymer. May contain small amounts of inorganic fillers or antimicrobial agent.

HEALTH HAZARD INFORMATION**Health Effects:**

None expected from normal handling. Although the polymer is inert with low oral or dermal toxicity, it is not recommended that the material be taken or used internally. Inhalation of foam dust may be harmful. Temperatures of in excess of 135°C encountered in any processing or other use will produce irritating or toxic fumes.

First Aid:

In case of overexposure to fumes, vapours or smoke, remove victim to fresh air. Render breathing assistance if needed and consult a physician. In case of eye irritation from contact of foam dust, fume, vapour and smoke, flush with ample quantities of water or suitable eyewash for 15 minutes.
Consult a physician.

PRECAUTIONS FOR USE

Exposure Limits: Not applicable.

Ventilation: None required under normal conditions. Ventilation required where material is processed with flame or hot cutting wires.

PERSONAL PROTECTION:

Respiratory Protection: None required unless fumes or dust is involved.

Protective Gloves: None required.

Eye Protection:

As appropriate around moving machine parts during fabrication or if dust protection required.

Flammability:

The material should be kept away from sparks, smokers' materials, open flame and from excessive heat. Smoking should be forbidden in areas where material is stored or processed.

Foam may burn rapidly with high heat and evolution of black smoke. Flammability ratings of small-scale laboratory tests are not to be taken as an indication of the material's behaviour in an actual full-scale fire.

DUNLOP FOAMS

Material Safety Data Sheet - Flexible Polyurethane Foam FR Grades (Cont.)

SAFE HANDLING INFORMATION

Storage & Transport:

Maintain adequate sprinkler protection where large volumes of foam are kept, e.g. warehouse, fabrication areas and storage rooms. Check for compliance with insurance regulations, local building codes or other legal requirements.

Spills & Disposal:

Waste may be baled or shredded for re-use. Dispose or landfill or incinerate as required by local or state regulation.

Fire/Explosion Hazard:

If ignited, the material may melt, producing flammable liquids. Burning produces toxic gases, such as carbon monoxide, oxides of nitrogen and hydrogen cyanide and intense heat and dense smoke.

Extinguishing Media: Dry chemical, water, carbon dioxide.

Special Firefighting Procedures: Wear self-contained breathing apparatus.

Other Information:

Refer to the Plastics Industry Association publication: "Flexible Polyurethane Foams - Its Uses and Misuses".

Contact Point:

Technical Services Co-Ordinator, South Dandenong Phone: (03) 9215 2020
Fax: (03) 9215 2015

Date: 7th November, 2008

The information supplied herein is presented in good faith and believed to be accurate to the best knowledge of the supplier. It is also predicated on normal use of the product. However, since conditions of use are beyond our control we make no warranties, expressed or implied as to the use of this information or to the suitability of product for a particular purpose.